



LIGHT SMART

Energy Efficient Lighting Solutions

UNI Fitting 2x28 T5 Tridonic Atco Ballast



Light Smart UNI Fitting 2x 28W Surface Mount

Introducing our new range of T5 2 X 28w Slimline Commercial Light fitting. Our Light Smart 'UNI Fitting' has been manufactured for use within all commercial applications and comprises of the latest energy efficient Tridonic Atco control gear.

The Light Smart T5 2 X 28w 'UNI Fitting' uses a larger footprint which enables less patch work when replacing older fittings in pre-existing buildings, while still keeping a sleek and slimline appearance in new applications.

Specifications:

- Tridonic Atco PC T5 Pro Ip 2x28W Electronic Control Gear
- Gloss White Powder Coated 0.5 mm Steel Chassis
- 0.4mm Thick Clear Acrylic Diffuser with Interlocking Side Skirts
- 4x VDE Lamp Holders
- 0.2mm High Quality Alanod 320G Reflector
- Large 0.4mm Diameter Terminal Block
- 2 x Cool White Tri Phosphorus 28W Light Smart T5 Tubes
- Quick Release End Caps with Fastening Screw
- Small Parts Bag Supplied eg. Plugs, Screws and Plastic Feet
- Dimensions 1200mm x 208mm x 70mm

Technical:

• True Power (watts)	56
• Apparent Power (watts)	58
• Voltage	244
• Current (amps)	0.236
• Power Factor (pf)	0.967
• Lux at 2 metres	385 lux

DISTRIBUTED BY:



Sparky Supplies Pty Ltd

14 William Street
Mile End
SA 5031
E: sales@sparkysupplies.com.au

Ph: 08 8234 6655
Fx: 08 8234 6656

Unit 2, 152 Commercial Road
Salisbury
SA 5108
E: salisbury@sparkysupplies.com.au

Ph: 08 8258 2219
Fx: 08 8258 8490

